

# SEMI-SILENT PETROL GENERATORS

FULL SPARE PARTS BACK-UP

WITH AVR



MADE TOUGH FOR AFRICA™



H6000



H9000E



H13000E

NEW



Control panel H9000E



Control panel H9000E/D



Control panel H13000E



Control panel H13000E

1ph/3ph DUAL UNIT

SINGLE PHASE

THREE PHASE

- Ideal for home and office use
- Compact and light-weight
- Automatic Voltage Regulation
- Standard SA 3-pin plug sockets
- Large fuel tank capacity
- Direct-coupled mounted in roll-over frame
- Wheel trolley options on H9000 & H13000

## HOFFMANN POWER

MODEL	H3000/E	H6000/E	H9000E	H9000E/D		H13000E	
kVA rating	3 kVA	6 kVA	8 kVA		10 kVA		
Output amps (ph)	13	26.1	36	30.4	10.1 amps p/hp	41	18.1 amps p/ph
Output volts	220			220/380			
Max engine speed (rpm)	3000						
Starting method	Recoil/electric						
Regulation	AVR						
Structure	Open with large fuel tank			Open with large fuel tank on wheels			
Nett weight (kg)	45	86	94	96		143	
Fuel tank capacity (L)	15		25		48		
Engine type	HX6.5	HX13	HX16 (460cc)		HX18 (622cc)		